

## ERRATUM / ERRATUM

**Erratum: Combined effects of reinforcement and prefabricated vertical drains on embankment performance****Allen Lunzhu Li and R. Kerry Rowe**

**Ref.:** Can. Geotech. J. **38**: 1266–1282 (2001).

The hydraulic conductivity change index,  $C_k$ , reported in Table 1 (Soil model parameters) of the above paper, should have been 1.25 for soils A and B, respectively.

In Appendix: A worked sample of the above paper and step (6), the back-calculated  $t_{O/C}$  should be 624 h instead of 186 h. Using eqs. [9] and [10] and  $C_{N/C}$ , the calculated  $\bar{U}_{N/C}$  is 5.8% at  $t = 9$  months, which should be at  $t = 810$  h at EOC. Using eq. [8], the calculated  $\bar{U}_f$  should be 42.1% instead of 42.5%. For step (7): the  $\bar{U}_f$  value of 0.425 should be 0.421 and the calculated  $\Delta s_{uf}$  value should be 2.57.

Received 26 May 2004. Accepted 26 May 2004. Published on the NRC Research Press Web site at <http://cgj.nrc.ca> on 2 July 2004.

**A.L. Li and R.K. Rowe.**<sup>1</sup> Department of Civil Engineering, Ellis Hall, Queen's University, Kingston, ON K7L 3N6, Canada.

<sup>1</sup>Corresponding author (e-mail: [kerry@civil.queensu.ca](mailto:kerry@civil.queensu.ca)).

